

Steel-Timber Hybrid Floor Vibrations in Life Science Laboratory Buildings

Ian Neill
Associate, LeMessurier



**CTBUH 2022
Steel-Timber Conference**

Steel-Timber Hybrid Floor Vibrations in Life Science Laboratory Buildings

Introductions

- Presenter



Structural Engineer
Ian Neill, PE
LeMessurier
Associate

- Contributors

- Perkins & Will

Jacob Werner

Elizabeth Mikula

- Jensen Hughes

Jeremy Liebowitz

- Acentech

Jeff Zapfe

Rose Mary Su

- LeMessurier

Mike Gryniuk

Mithila Madvahan

Eric Johnson

Emma Rubin

Priya Dewan

Sebastian Torrente

Life Sciences Tall Buildings



Fenway Center Phase 2, Boston, MA
Image courtesy of Gensler and IQHQ



Seaport Parcels N & P, Boston, MA
Image courtesy of Morris Adjimi Architects

Lab Building Design Considerations

- Control Areas / Hazardous Uses
- Fire ratings
- Loading docks
- Elevator access
- Acoustics
- Air handling – large ducts
- Tenant MEP
- Large floor-to-floor height
- **Floor Vibrations for Sensitive Equipment**




Images courtesy of Perkins&Will



Vibration Limits for Occupant Comfort

- Typical vibration criteria for offices and residences
- Criteria is typically expressed as an acceleration in %g





Vibration Limits for Sensitive Equipment

Designation	Tolerance Limit $\mu\text{in/s}$	Applicability
--	32,000	Ordinary workshops
--	16,000	Offices
--	8,000	Computer equipment Residences
--	6,000	Hospital patient rooms
--	4,000	Surgery facilities, laboratory robots Bench microscopes up to 100x, operating rooms
VC-A	2,000	Microbalances, optical comparators, mass spectrometers Industrial metrology laboratories, spectrophotometers Bench microscopes up to 400x
VC-B	1,000	Microsurgery, microtomes and cryotomes for 5 to 10 μm slices Tissue and cell cultures, optical equipment on isolation tables Bench microscopes at greater than 400x, atomic force microscopes


Current Construction Practice

- Steel frame construction
- Normal weight concrete slab-on-deck
- Steel-concrete composite



Steel-Timber Hybrid Floor System


- Framing system as described in AISC DG 37
- Steel floor beams and girders
- 5-ply CLT timber floor panels spanning between floor beams
- 1" acoustic layer
- 2" normal-weight concrete topping
- STC = 50 to 60
- IIC = 40 to 50






Why Steel-Timber Hybrid?

- Mass Timber is a differentiator in the marketplace
- High span-to-depth ratio compared to All-Timber
- Versatility of steel
- Embodied Carbon
- **Does Steel-Timber Hybrid meet vibration performance?**

Floor Vibration Study





Floor Vibration Design Guides



Vibration Analysis Methods

- AISC DG-11 Simplified Method
 - Approximate and conservative
 - Material-specific calibrations
- **AISC DG 11 Frequency Response Function (FRF)**
- CCIP-016 Design Guide (Cement and Concrete Industry Publication)
- Walking path time history analysis
 - Most precise
 - Most difficult to implement



Modal Analysis


3x3 Bay System

Velocities measured at center
of interior bay

Free edge at perimeter


1-story column stiffness
included

Multiple modes of vibration
considered




Composite Section Properties


- Full composite action with CLT assumed for vibration analysis
- Additional stiffness could be achieved through composite action with the concrete topping
 - Composite action with concrete topping was not assumed for baseline study
- Limited testing and observations for composite action of topping above acoustic layer




Modal Analysis Results



- Low correlation between mode shape and excitation
- Good vibration performance




Variability in Vibration Performance



Walking Excitation at
Middle of Center Bay


- Center-bay response used for comparison purposes
- Comprehensive evaluation of a building floor plate needs to account for many factors and performance will not be uniform




Walking Excitation at
Middle of Corner Bay

Design Results and Vibration Performance


STEEL



STEEL-TIMBER



ALL-TIMBER



Total Structure Depth

2'-10"

+5" more depth than steel

+1'-7" more depth than steel

Girder Size

W27x84

W30x90

11½ x 43⅝

Beam Size

W21x48

W24x68

11½ x 35⅝

FRF Vibration Velocity
(Center Bay)**

2300 mips

2800 mips

2700 mips


(3200 at Corner Bay)

Composite w/ conc topping
1600 mips

Composite w/ conc topping
1500 mips

Embodied Carbon Performance

- Floor framing and slab only
 - Columns, foundations, façade, etc not included
- Results for Hybrid and All-Timber are reported both with and without the effects of Biogenic Carbon
- Results include Life-Cycle Assessment Stages A to C
- Larger variability in Impact Factors for Timber than for other materials



Summary

- Steel-Timber Hybrid balances the versatility of steel with the benefits of Mass Timber
- Steel-Timber Hybrid can achieve good vibration performance while minimizing depth of structure compared to the All-Timber option
- Embodied Carbon performance of Steel-Timber Hybrid is an improvement over traditional construction

Thank you!



LeMessurier.

CTBUH Steel-Timber Hybrid Conference – May 23, 2022